

## CUSTOMER SPECIFICATION SHEET For 3T/AST INFRARED PYROMETER

Customer Name: \_\_\_\_\_

Address: \_\_\_\_\_

Tel: \_\_\_\_\_ Fax: \_\_\_\_\_

Email: \_\_\_\_\_ Attn: \_\_\_\_\_

### Sensor Model

Quantity	Model	Measurement Range	Emissivity Range	Sport from a Distance of 1M
	AE3000 Aluminium Press Exit	<b>350 – 650 °C</b> 660 – 1,200 °F	0.1-0.6	20mm
	AB3000 Aluminium Billet	<b>300 – 600 °C</b> 570 – 1,110 °F	0.1-1.0	20mm
	AC3000 Aluminium Post Quench	<b>200 – 600 °C</b> 390 – 1,110 °F	0.1-0.6	20mm
	AD3000 Aluminium Die	<b>300 – 650 °C</b> 570 – 1,200 °F	0.1-1.0	20mm
	AM3000 Molten Aluminium	<b>450 – 900 °C</b> 840 – 1,650 °F	0.1-1.0	20mm
	P3000	<b>300 – 1000 °C</b> 570 – 1830 °F	0.1-1.0	20mm
	S3000	<b>1000 - 2000 °C</b> 1830 – 3,630 °F	0.1-1.0	2.5mm

### Option (More options will be provided in quotation)

Quantity	Item
	SD3000 Logging PC Software
	P110 Display (Single Channel)
	P300 LCD Display (Multi Channel)
	Analog Output
	Alarm
	PS3000 Scanning System

Price Term: Deliver to Customer Site in RMB.

Price Term: DDU Customer Site in USD.

Amkes, Inc.

5F-5, No. 147, Ta Shun 2nd Road, Kaohsiung, Taiwan

Tel: +886-7-386-8022

Fax: +886-7-381-4537

Website: <http://www.amkes.com>

E-Mail: [info@amkes.com](mailto:info@amkes.com)